
## TC4 Series 14 SEER Split System Air Conditioners

Model		TC4B2422S	TC4B3022S	TC4B3622S	TC4B4821S	TC4B6021S		
Unit Supply Voltage		208-230V, 1 Phase, 60Hz						
Normal Voltage Range <sup>1</sup>		187 to 252						
Minimum Circuit Ampacity		14.8	18.4	19.6	25.7	31.7		
Max. Overcurrent Device Amps <sup>2</sup>		25	30	30	45	50		
Min. Overcurrent Device Amps <sup>3</sup>		15	20	20	30	35		
Compressor Type		Scroll	Scroll	Scroll	Scroll	Scroll		
Compressor	Rated Load	11.2	14.1	14.7	19.5	24.3		
Amps	Locked Rotor	60.8	73.0	75.0	130.0	144.2		
Crankcase Heater		No	No	No	No	No		
Factory External Discharge Muffler		No	No	No	No	No		
HS Kit Required with TXV <sup>4</sup>		No	No	No	No	No		
Fan Diameter Inches		22	22	22	24	26		
Fan Motor	Rated HP	1/8	1/8	1/4	1/4	1/4		
	Rated Load Amps	0.80	0.80	1.30	1.30	1.30		
	Nominal RPM	1075	1075	850	850	850		
	Nominal CFM	1950	2850	3225	3500	4300		
Coil	Face Area Sq. Ft.	12.21	12.21	13.83	18.74	23.4		
	Rows Deep	1	1	1	1	1		
	Fins/Inch	23	23	23	23	23		
Liquid Line Set OD (Field Installed)		3/8	3/8	3/8	3/8	3/8		
Vapor Line Set OD (Field Installed) <sup>5</sup>		3/4	3/4	3/4	7/8	1-1/8**		
Unit Charge (Lbs Oz) <sup>6</sup>		3 - 12	3 - 14	4 - 1	4 - 15	5 - 12		
Charge Per Foot, Oz.		0.62	0.62	0.62	0.67	0.75		
Operating Weight Lbs.		135	140	145	200	205		

- 1. Rated in accordance with AHRI Standard 110-2012, utalization range "A".
- 2. Dual element fuses of HACR circuit breaker. Maximum allowable overcurrent protection.
- 3. Dual element fuses or HACR circuit breaker. Minimum recommended overcurrent protection.
- 4. See Hard Start Kit Accessory Installation Manual for Hard Start Kit part number for each model.
- 5. For applications with non-standard vapor line sizes, see the Applications & Accessories section of the Technical Guide.
- 6. The Unit Charge is correct for the outdoor unit, smallest matched indoor unit, and 15 feet of refrigerant tubing. For tubing lengths other than 15 feet, add or subtract the amount of refrigerant, using the difference in actual lineset length (not the equivalent length) multiplied by the per foot value.



## **DIMENSIONS**

Unit Model		mensions Inches)	Refrigerant Connection Service Valve Size		
	Α	В	С	Liquid	Vapor
TC4B2422S	26-3/4	29 - 1/4	29 - 1/4		
TC4B3022S	26-3/4	29 - 1/4	29 - 1/4		3/4
TC4B3622S	30	29 - 1/4	29 - 1/4	3/8	
TC4B4821S	33 - 1/4	35 - 1/4	31 - 3/4		7/8
TC4B6021S	36 - 1/4	38	34 - 1/4		7/8*

\* \* Adapter fitting must be field installed for the required 1-1/8" line set. All dimensions are in inches and are subject to change without notice. Overall height is from bottom of base pan to top of fran guard. Overall length and width include screw heads.